# **Real World JFR**

Experiences building and deploying a continuous profiler at scale

Jean-Philippe Bempel





• Quick introduction to JDK Flight Recorder (JFR)

• JFR at Datadog

• Lessons learnt



# **Quick Intro to the JDK Flight Recorder (JFR)**

- Data Flight Recorder for the JVM
- Records information about the JVM and the application
- Low overhead
- Powerful APIs and Tooling
- Can be used to solve a range of different problems





# Availability of JFR

• OpenJDK/HotSpot

• Open sourced since JDK 11

• Backported to OpenJDK 8u262/272



• Events recorded into thread buffers





- Events recorded into thread buffers
- When full, copied into global buffer





- Events recorded into thread buffers
- When full, copied into global buffer
- Can be configured to keep on overwriting/reusing buffer



- Events recorded into thread buffers
- When full, copied into global buffer
- Can be configured to keep on overwriting/reusing buffer
- ... or emit to disk



## Low Overhead

- High performance flight recording engine
  - Invariant TSC for time stamping
  - Thread local native buffers
  - Efficient format for low overhead event emission
- High performance data collection
  - Access to data already collected in the Java runtime
  - Built into the JVM/JDK skip abstractions
- Trying hard not to change runtime characteristics



## **Other Properties of JFR**

- Self describing chunks of information
- Self contained chunks
- Chunk rotations will happen when
  - Start / Stop recording
  - Create a snapshot



# **Quick Demo JFR**

# **JFR at Datadog**



## JFR at Datadog

- Continuous capture offers a lot of interesting capabilities
  - Always data available when things go bad
  - Possibility to break down profiling data
    - Time/Thread
    - Context
  - Continuous stream of data for analysis and statistics
- Is continuous capturing economically feasible?
  - What is the data rate?
  - What is the actual performance overhead?



































## **Continuous Profiler figures**

- Actually works surprisingly well at incredible scale
  - Datadog is intaking terabytes of JFR data per minute
  - Datadog is intaking all data from every Java process
- Recording data size 5 (2 compressed) MiB per minute
- Corresponds to around 100k events
- Normally one chunk per minute
- Cpu Overhead usually < 2%
- Cost for continuously repeating the metadata ~= 0.5%



## JFR template specially crafted

• 2 flavors provided by OpenJDK

- Customize one with:
  - Allocation profiling
  - Exceptions
  - Exec Sampling 20 ->9 ms
  - Thresholds adjusted (VM operation, File IO, Monitors, Threads)



### **Overhead assessment**

• Spring petclinic application

• request processing time too short

• More difficult to assess any overhead statistically significant

• Also not representative to real workload



#### **Overhead assessment**

• Custom Spring petclinic

• Increase processing time for 100ms per request

• Increase In-memory database entries



#### **Overhead measurements**

• Heap & GC

• CPU from /proc/<pid>/stat get total cpu ticks since startup



# **Lessons Learnt**



#### JFR at Scale

- All these observations are from using JFR at scale
- Very varying kinds of loads and applications
  - "Typical" long running Java microservices
  - Scala / Akka / high throughput messaging
  - Async / Reactive
- From casual use of the JDK Flight Recorder, you may not encounter any of these problems



## **Exception Profiling**

- Built in JFR exception profiler can be configured to capture all Exceptions or only Errors.
- Captures all, caught or uncaught (event generated on exception creation)
- Great to at least enable Errors?



"Error is the superclass of all the exceptions from which ordinary programs are not ordinarily expected to recover."



# **Errors (And Exceptions) Outside the Ivory Tower**

- One of the most popular and widely used Java Libraries:
  - JavaCC => Lucene => Elasticsearch
  - Enormous amount of errors
  - Subclass named LookAheadSuccess
  - Used for control flow in a parser

But exception profiling is great!
 -> Invent new exception profiler





## **New Exception Profiler**

- Get a count of exceptions per type
- Sample the first thrown exception of each type
- Subsample to try to hit a target rate
  - $\circ~$  Use inspiration from PID controllers
  - $\circ~$  Evenly spread across time





## **PID controller**

• Control loop mechanism



• using feedback loop

• apply correction based on error with P, I D terms























## **Allocation Profiling in JFR**

- Allocation profiling introduced in JFR
  - Introduced in 7u40 (2013)
  - Has two paths/events New TLAB / outside TLAB





## **Allocation Profiling in JFR**

- Allocation profiling introduced in JFR
  - Introduced in 7u40 (2013)
  - Has two paths/events New TLAB / outside TLAB





## **Allocation Profiling in JFR**

- Allocation profiling introduced in JFR
  - Introduced in 7u40 (2013)
  - Has two paths/events New TLAB / outside TLAB





# **The Dangers of Allocation Profiling**

- Normally has quite good runtime performance and data production rate
- These days though...
  - 96+ core beasts
  - allocation hungry services (e.g. stream processing beasts)
- Event rate depends on factors like
  - number of threads
  - size and number of allocations



## **Allocation Profiling Performance Problems**

jfr summary recording.jfr

Version: 2.1 Chunks: 2 Start: 2020-07-22 07:23:25 (UTC) Duration: 60 s		
Event Type	Count	Size (bytes)
jdk.ObjectAllocationInNewTLAB	437808	10011153
jdk.ZThreadPhase	25780	1142331
jdk.ThreadPark	18614	802953
jdk.ExecutionSample	13509	233323
jdk.ObjectAllocationOutsideTLAB	10620	231453
datadog.ExceptionSample	9421	348824
jdk.JavaMonitorWait	5199	171686
jdk.NativeMethodSample	4293	75900
jdk.ThreadSleep	3244	68124
jdk.ClassLoaderStatistics	1468	43716
jdk.BooleanFlag	1236	43028
jdk.ThreadAllocationStatistics	809	13859
jdk.ThreadCPULoad	619	13449



## **Allocation Profiling Performance Problems**

- Hashcode problem JFR constant pool (solved)
- Still too much data to handle
- Solution -> new allocation profiler in JFR (JDK 16+)



## **New Allocation Profiler**

- Take the idea from the JVMTI (JDK 11+) allocation sampler (i.e. average amount of memory between samples)
- Inspiration from PID controllers control data production rate
- Many nice qualities:
  - Controllable data budget
  - Actual individual samples (time, thread)
  - Allocation since last sample for weighting (total allocation pressure)



#### **New Allocation Profiler**



TLAB



# Memory leak profiler: OldObjectSample

- Interesting for solving memory leaks
  - Allocation Stacktrace
  - Allocation Time
  - Type
  - Array size
  - Reference chain



## **OldObjectSample Problems**

• Allocation sample are kept into a queue





# **OldObjectSample Problems**





# **OldObjectSample Problems**





## **ConstantPool explorer**

🜠 JDK Mission Control								10-00	σ	×
Eile Edit Navigate Window I	Help									
🖉 JVM Browser 🗄 Outline	🛋 💛 8 🗖 🗆	∞ prof-analyzer-01.jfr 🛛								- 0
a <sup>®</sup> Lock Instances ₄\$ File I/O	^	▶ Constant Pools								
📲 Socket I/O		Search the table								
Co Method Profiling		Constant Bool News	C	Ci	Tatal Cine (0()					•
Second Exceptions		Constant Pool Name	Count	Size	Iotal Size (%)					
Thread Dumps	_	Jdk.types.Symbol	13272	688 KIB	17.2 %					-
V 🚱 JVM Internals		Jdk.types.StackTrace	10066	2.84 MIB	72.7%					
Garbage Collections	5	jdk.types.Method	5757	151 KiB	3.77 %					
GC Configuration		Java.lang.Class	2480	145 KiB	3.63 %					
> 😪 Compilations	_	java.lang.Thread	1272	61.1 KiB	1.53 %					
G Class Loading	_	jdk.types.Package	364	9.88 KiB	0.247 %					
<b>WM</b> Operations	_	jdk.types.Bytecode	239	2.55 KiB	0.0638 %					
TLAB Allocations	_	jdk.types.OldObject	169	1.82 KiB	0.0456 %					¥ .
✓	_	lambda								
• Processes		Constant Value								^
Environment Variabl	les	com datadog profiling analyzer stages.	DownloadStage\$\$Lambda\$103	0+0x000000080	01354b80/19788130	004				
System Properties	_	com.datadog.profiling.aggregation.par	ser. IfrSampleDefinitions\$\$Lar	bda\$1744+0x0	0000008015716d0/	851710768				
Wative Libraries	_	software amazon awssdk core internal	atta nineline stages MakeAsva	HttpRequestSt	age\$\$Lambda\$386	+0×00000008010	06710/81445899			
✓ ► Recording		lambda\$finalizeSdkHttnFullRequest\$0	http://pipeinie.stuges.inukeAsyn	inteprequests	ugesseambaassoo	10,0000000000000000	500710701445055			
Constant Pools		lambda\$wrannedWith\$4								
Se Event Browser	~	lambda\$wrappedWith\$5								
	📑 😚 🗆 🗖	software amazon awsidk http nie netty	internal Perpense Handler <sup>®</sup> Pul	licharAdaptor	1\$\$1 ambda\$716+0	000000080121	620/2022670220			
Field Velue		lambda\$doInOrder\$4	.internalitesponserialitater a	Juguer Auguer 4	1992011500071010		5050/2025070220			
Field Value		lambuaşuomoruerş4								~
o events		= Stack Trace 🚸 Flame View					k 7 K	te: 🔘 🎤	8	
		Stack Trace			Count	Percentage				

## **OldObjectSample Solutions**

• Having a second stacktrace repository specific for the event





# **CPU Profiling**

**Execution Sample events** 

- Pros
  - $\circ~$  Very cheap both in memory and overhead
  - Pretty much constant overhead
  - Not safepoint biased (like AsyncProfiler)
- Cons

Not sampling all threads
 (e.g. JVM native threads/native library threads)

-> Compensate unaccounted CPU time using other events

# **CPU Profiling**

- JFR would do well with a proper CPU profiler
  - Sample taken when certain CPU time elapsed...
  - ...no matter the thread
  - Nice APIs available today... (e.g. perf\_event\_open)
  - ...backed by PMU (not in containers though)



## Latency outliers vs Wall-Clock

- JFR has events for thread halts
  - Provide more than just a stacktrace
  - Provide exact wall-clock timing of the halts
- Happen too often
  - Must be limited to outliers only
  - Uses thresholding to keep volume down
- Thresholding is problematic
  - Edge cases
  - Statistical skew
  - $\circ~$  Hard to know if you've missed somethings

## **Best of Both Worlds?**

- Subsample / Rate limit the events (PID thinking FTW)
- Add a proper wall clock profiler for JFR...

#### How about adding Event#commit(Thread)?

(Events might also want to add an annotation whether or not the thread state should be captured or not.)



# Wrap Up





• JFR is more than a profiler and can be used in production

• Exception, allocation and leak profiler can increase overhead

• Solutions to this are coming to your JDK near you, soon!



#### JMC 8 is Released!

• Tutorial:

https://github.com/thegreystone/jmc-tutorial
(Feel free to fork and do pull requests for the Tutorial! :))

 JShell for JMC-core (jmc-jshell): <u>https://github.com/thegreystone/jmc-jshell</u>



### References

- JDK Mission Control GitHub Repo
- Marcus Hirt's Blog
- <u>Continuous Profiling Blog</u>
- Improved JFR Allocation profiling in JDK 16
- Adaptive Sampler: <u>Java impl</u> & <u>JFR impl</u>
- OldObjectSample PR





🤇 @jpbempel